








№	Материалын нэр	Хэмжих нэгж	Зураг	Техник үзүүлэлт
1	Cisco Catalyst WS-C3750X-24T-S бл.питания C3KX-PWR-350WAC	ШТ		<ol style="list-style-type: none"> Switching Fabric 160 Gbps DRAM 256 MB (512 MB for 3750X-12S and 3750X-24S) Flash 64 MB (128 MB for 3750X-12S and 3750X-24S) Total VLANs 1005 C3KX-NM-1G, Four GbE port network module C3KX-PWR-350WAC, AC Power Supply
2	Cisco SG300-28P 28-port Gigabit Managed Switch	ШТ		<p>Release Date 01-AUG-2010 Capacity: 4K Active VLANs MAC Address Table Size: 16k entries Maximum Storage Temperature: 158 F Ports: 26 x 10/100/1000 + 2 x combo Gigabit SFP Interfaces: 24 x 10Base-T/100Base-TX/1000Base-T - RJ-45 – 2 x 10Base-T/100Base-TX/1000Base-T - RJ-45; 1 x console - 9 pin D-Sub (DB-9) - management; 2 x SFP (mini-GBIC) Ram: 128 MB Authentication Method: Secure Shell (SSH), RADIUS, TACACS+ Voltage Required: AC 120/230 V (50/60 Hz)</p>

3	Шилэн кабелийн төгсгөлийн хайрцаг FDF-8 port /солонгос/	ШТ																																
4	3M 497AJM 120V Portable Electronic Vacuum Cleaner	ШТ		<table border="1" data-bbox="1346 418 2039 727"> <thead> <tr> <th>Property</th> <th>Typical Value</th> <th>Test Method</th> </tr> </thead> <tbody> <tr> <td>Model 497AJM</td> <td>120VAC, 50/60 Hz, 6.0 amps</td> <td>Supplier</td> </tr> <tr> <td>Model 497ABF</td> <td>220/240VAC, 50/60 Hz, 4.25 amps</td> <td>Supplier</td> </tr> <tr> <td colspan="3">Dimensions</td> </tr> <tr> <td>Length</td> <td>17.8 inches (45.2 cm)</td> <td>3M Internal</td> </tr> <tr> <td>Width</td> <td>7.8 inches (19.7 cm)</td> <td>3M Internal</td> </tr> <tr> <td>Height</td> <td>9.3 inches (23.5 cm)</td> <td>3M Internal</td> </tr> <tr> <td>Weight</td> <td>11 lbs.</td> <td>3M Internal</td> </tr> <tr> <td>Sound pressure Level</td> <td>74.0 dBA</td> <td>ISO Standard 11201; 1st edition 1995-12-15</td> </tr> <tr> <td>Motor</td> <td>1 HP</td> <td></td> </tr> </tbody> </table> <p data-bbox="1346 734 2039 756">Continuous duty rated with one sealed ball bearing and one sleeve bearing lubricated for life.</p> <p data-bbox="1346 763 2039 786">Thermally protected with automatic reset.</p> <p data-bbox="1346 792 2039 815">Electronics Vacuum 497 Series comes complete with:</p> <ul data-bbox="1346 821 2039 964" style="list-style-type: none"> Hose, 10 ft SV-SH32 – 78-8063-2418-8 Wand, SV-WA2 – 78-8063-1540-0 Crevice Tool, SV-CN1 – 80-6104-7958-8 Crevice Tool Brush, SV-CB1 – 80-6104-7957-0 Needle Nozzle – 78-8063-1549-1 <p data-bbox="1346 971 2039 993"><i>(Needle Nozzle not included with 3M™ Service Vacuum 497 Series)</i></p>	Property	Typical Value	Test Method	Model 497AJM	120VAC, 50/60 Hz, 6.0 amps	Supplier	Model 497ABF	220/240VAC, 50/60 Hz, 4.25 amps	Supplier	Dimensions			Length	17.8 inches (45.2 cm)	3M Internal	Width	7.8 inches (19.7 cm)	3M Internal	Height	9.3 inches (23.5 cm)	3M Internal	Weight	11 lbs.	3M Internal	Sound pressure Level	74.0 dBA	ISO Standard 11201; 1st edition 1995-12-15	Motor	1 HP	
Property	Typical Value	Test Method																																
Model 497AJM	120VAC, 50/60 Hz, 6.0 amps	Supplier																																
Model 497ABF	220/240VAC, 50/60 Hz, 4.25 amps	Supplier																																
Dimensions																																		
Length	17.8 inches (45.2 cm)	3M Internal																																
Width	7.8 inches (19.7 cm)	3M Internal																																
Height	9.3 inches (23.5 cm)	3M Internal																																
Weight	11 lbs.	3M Internal																																
Sound pressure Level	74.0 dBA	ISO Standard 11201; 1st edition 1995-12-15																																
Motor	1 HP																																	
5	3M SV-MPF2 Vacuum Filter part number:78-8005-5350-1	ШТ		<p data-bbox="1346 1123 2039 1146">Manufacturer: Compatible 3M</p> <p data-bbox="1346 1153 2039 1175">Model: SV-MPF2</p> <p data-bbox="1346 1182 2039 1205">Type 2</p> <p data-bbox="1346 1211 2039 1234">For: 497AJM vacuum</p> <p data-bbox="1346 1240 2039 1263">RoHS compliant</p> <p data-bbox="1346 1269 2039 1292">Remove toner from laser printers and copy machines</p> <p data-bbox="1346 1299 2039 1321">Pleated filter</p> <p data-bbox="1346 1328 2039 1351">Encased in plastic</p>																														

6	Madell 850B Hot Air Rework Station	LIT		<p>Precise airflow and temperature adjustments. Good for QFT, SOP, PLCC chips and other components. Hot air temperature 100°C to 480°C. Power consumption: 560W(max.). Digital temperature display. Delayed air pump shut off for hot air gun and nozzle protection. Safe soldering and desoldering with the included nozzles. Four nozzle options: A1125, A1126, A1130, A1170. 110V power supply. Total 33 nozzles available. The nozzles are standard sizes and are compatible with Hakko and other hot air soldering stations. One-year warranty. Repair services or replacement will be done by us.</p>
7	Model: KPS3010D 30V 10A Precision Variable Adjustable Digital Regulated DC Power	LIT		<ul style="list-style-type: none"> - Input voltage: 110V±10% 60Hz - Output voltage: DC 0-30V Continuous adjustable - Output current: DC 0-10A Continuous adjustable - Display resolution: voltage: 0.1V , current 0.1A. - Display precision: ±1% ±1digit - Voltage stabilization: 0.05% +1mV - Current stabilization: 0.1% +10mA - Load stabilization: CV 0.1% +1mV / CC 0.1% +10mA - Ripples and noises: CV10mV(RMS)/ CC20mA(RMS) - Cooling way: Intelligent temperature control fan. if the temperature is higher than 50°C - Working conditions: 14°F to 104°F Relative humidity < 80% - Storage conditions: -4°F to 176°F Relative humidity < 80% - Body Dimension(LxWxH): 10 1/4" x 5" x 5 7/8" (26x12.6x14.8cm) - Power Supply: 110V AC
8	Excel 1U Keystone Jack 19" cFrames Patch panel Part No:100-028, Excel Cat	LIT		<p>Category: Keystone Jack dependent Suitable for number of outlets / modules: 24 Colour: Chrome Mounting method: 19 inch mounting Number of rack units (RU): 1 Height: 44 mm Width: 483 mm Depth: 155 mm</p>

9	RAM DDR-3 4Gb	ШТ		<p>4GB DDR3 1600 MHZ PC3-12800 240PIN DIMM For AMD Motherboard Desktop memory Brand new and high quality 4GB PC3-12800 1600MHZ High Density (128Mx4 Chipset) Original Chips,Double-Sided 16chips 240 Pins, Desktop Memory Dual Channel Support 1.5V CL11</p>
10	Хардны суурин залгуур HDD Docking station	ШТ		<ol style="list-style-type: none"> 1.COMPATIBILITY OF HARD DISK BASE:The Awolf HDD docking station is compatible with all IDE and SATA 2.5 "/3.5" hard disk, A single SATA hard disk support max-capacity up to 8T, Total 12TB, with 4A power adaptor. it can support a IDE and a SATA hard disk, two USB and a storage card work normally at the same time. 2.OTB(ONE TOUCH BACKUP): When the operation system crash and can't start up or the system files lost owing to the virus, we can delete the Trojan virus and the affected files, then just press the"OTB"button one time to recover and backup these important files. 3.THE MULTI-FUNCTIONAL FRONT PANEL: The Awolf ide hard drive docking station with front interface can read CF/XD/MS/SD/TF card and USB Flash , can also connect the USB mouse and keyboard (don't support these cards to use at the same time).When the ide hdd docking station connects to the power adaptor, you can fast charge for phone/pad. 4.SUPPORT MULTIPLE SYSTEMS:The Awolf Multi-function hdd ide docking station support Windows/Lunix/Mac,etc. system, with powerful system storage expansion function, you can use it as entertainment video library for your HD equipment such as smart TV, HD set-top box, etc.. 5.SATETY AND WARRANTY: The usb hdd docking station is equipment with built-in anti overflow, overvoltage, leakage, short circuit, clutter and other protective mechanisms to ensure the safety of data transmission. We provide 1 year warranty , When you have any problem, our professional engineers will give you a satisfactory solution.

